

DA3200

25 MHz – 3000 MHz


The ultra wideband discone antenna



- Rugged 16 element discone.
- Ultra wideband design providing continuous coverage from 25 MHz to 3000 MHz.
- Ideal for professional, surveillance and monitoring applications.
- Designed and manufactured to exacting standards.
- Supplied with 15m of low loss 5D-2V coaxial cable.



■ Return loss chart




■ Specifications

Frequency range	25-3000MHz
Impedance	50Ω
Gain / dB	Max. 3dBi (100-3000MHz)
Connector	N socket
Weight	Approx. 1kg (cable excluded)
Rated wind velocity	50m/sec.
Dimensions	Height: 1.12m, diameter: 0.84m
Mast diameter accepted	25-50mm
Supplied accessory	15m coaxial cable (5D-2V) with N connectors.

- DA3200 is NOT intended for transmit purposes.
- Product design and specifications are subject to change without notice or obligation.
- ROHS compliant.

■ Vertical radiation pattern



AOR, LTD.
2-6-4, Misuji, Taito-Ku, Tokyo
111-0055, Japan
www.aorja.com mail@aorja.com

AOR USA, INC.
20655 S. Western Ave. Suite 112
Torrance, CA 90501, U.S.A
Phone: 310-787-8615 Fax: 310-787-8619
www.aorusa.com info@aorusa.com